

Product Specification



12-2 Plenum	Cross Section	Packaging
Spec No: S-023 Date: 4/12/2014 Approved By: Brian Rizzo		Box 500 Ft. Colors

Description									
12-2 Plenum, 12AWG, 2 Conductor, Stranded, Bare Copper, Class 3 Plenum & FT6 Rated for Commercial and other Plenum Audio Applications.									
Description <table><tr><td>Rated Voltage (V)</td><td>300</td></tr><tr><td>Rated Temperature (°C)</td><td>75</td></tr><tr><td>Product Standard Certification</td><td>c(UL) CMP or (UL) CL3P</td></tr><tr><td>Flame test</td><td>FT6</td></tr></table>		Rated Voltage (V)	300	Rated Temperature (°C)	75	Product Standard Certification	c(UL) CMP or (UL) CL3P	Flame test	FT6
Rated Voltage (V)	300								
Rated Temperature (°C)	75								
Product Standard Certification	c(UL) CMP or (UL) CL3P								
Flame test	FT6								
Application Power-limited circuit cables for use as fixed wiring within buildings (some are also marked for direct burial) principally for Class 3 and Class 2 circuits.									
Reference Standard: UL 13 & the customer's specification.									

Performance															
Electrical Characteristics (20°C) <table><tr><td>Max Conductor Resistance (Ω/KM)</td><td>5.76</td></tr><tr><td>Voltage</td><td>300 Volts RMS</td></tr><tr><td>Temperature</td><td>-20°C to 75°C</td></tr><tr><td>Min. Insulation Resistance (Ω/KM)</td><td>CMP-PVC: 100M</td></tr><tr><td>Dielectric Strength</td><td>AC-500V/1 Minute</td></tr><tr><td>Impedance (near by)</td><td>61 ± 3Ω</td></tr><tr><td>Capacitance (near by)</td><td>27 ± 1 pF/Ft</td></tr></table>		Max Conductor Resistance (Ω/KM)	5.76	Voltage	300 Volts RMS	Temperature	-20°C to 75°C	Min. Insulation Resistance (Ω/KM)	CMP-PVC: 100M	Dielectric Strength	AC-500V/1 Minute	Impedance (near by)	61 ± 3Ω	Capacitance (near by)	27 ± 1 pF/Ft
Max Conductor Resistance (Ω/KM)	5.76														
Voltage	300 Volts RMS														
Temperature	-20°C to 75°C														
Min. Insulation Resistance (Ω/KM)	CMP-PVC: 100M														
Dielectric Strength	AC-500V/1 Minute														
Impedance (near by)	61 ± 3Ω														
Capacitance (near by)	27 ± 1 pF/Ft														
Mechanical Characteristics <table><tr><td>Test Object</td><td>Jacket</td></tr><tr><td>Test Material</td><td>CMP-PVC</td></tr><tr><td>Before Tensile Strength (kg/mmP2)</td><td>≥1.05</td></tr></table>		Test Object	Jacket	Test Material	CMP-PVC	Before Tensile Strength (kg/mmP2)	≥1.05								
Test Object	Jacket														
Test Material	CMP-PVC														
Before Tensile Strength (kg/mmP2)	≥1.05														
Sequential footmarks applied every four feet in conjunction with the print legend. "XXX/XXX" Stands for Length. eg: 000/1000; 004/0996; 008/0992...															

Construction									
Conductor Component AWG Construction (± 0.008mm) Stranded Dia. (±0.05mm) Insulation Nom. Thickness (mm) Insulation Dia. (±0.05mm)	Stranded Bare Copper 2C 12 65/0.247 2.30 CMP-PVC 0.25 2.85								
Ripcord Jacket Nom. Thickness (mm) Outer Dia. (±0.10mm)	210 Dx6 Nylon Thread CMP-PVC 0.33 6.36								
Insulation/Conductor Colors <table><tr><td>Component</td><td>1. Red</td></tr><tr><td></td><td>2. Black</td></tr><tr><td>Jacket Colors</td><td>Pantone White</td></tr><tr><td></td><td>Pantone Black</td></tr></table>		Component	1. Red		2. Black	Jacket Colors	Pantone White		Pantone Black
Component	1. Red								
	2. Black								
Jacket Colors	Pantone White								
	Pantone Black								

Compliance			
		CL3P	FT6

Jacket Marking (Black)

ICE CABLE SYSTEMS 12-2 PLENUM SPEAKER CABLE 12AWG 2C E312434-22 c(UL) CMP FT6 75C OR E301442-22 (UL) CL3P ROOM: ENT KIT NK FAM LR DR POWD OFF POO PAT
MBR MBA BR1 BR2 BR3 BR4 BR5 GAR GYM 1 2 3 4 5 6 "ROHS" XXX/XXX FT