

 signature

# Kick Your Audio Up a Notch

Signature by Episode 5 Series

Kick your audio install up a notch with the 5 Series, crafted with a polypropylene woofer and adjustable, silk dome tweeter - both with vacuum-deposited titanium.



## Sound Science

Signature by Episode delivers superior audio through three scientific philosophies: low distortion, wide dispersion, and flat frequency response - providing unmatched audio accuracy for a fully-immersive lifelike experience.

## Accurate Reproduction

Using flat frequency response, Signature by Episode delivers audio without frequency bias, producing sound true to what the artist intended and giving you the most accurate and lifelike experience possible.

## Adaptable Listening

Signature by Episode delivers the same high-quality sound at both low and high volumes by using lighter, stiffer driver materials with greater excursion and tweeters that can play lower into the frequency band.

## Low-Profile

Your speakers will blend in wherever they're placed thanks to our thin-bezel paintable grilles and affordable flush-mount brackets that provide a smooth, minimalistic finish.

VISIT US AT  
[episodespeakers.com](http://episodespeakers.com)

# Signature by Episode 5 Series

	SIG-54-IC	SIG-56-IC	SIG-58-IC	SIG-56-ICSURR	SIG-58-ICSURR	SIG-56-POINT	SIG-56-ICDVC	SIG-58-ICDVC	SIG-56-IW	SIG-58-IW	SIG-56-IWSURR	SIG-56-IWDVC	SIG-56-IWLCR
Placement	In-Ceiling	In-Wall	In-Wall	In-Wall	In-Wall	In-Wall							
Type	Standard	Standard	Standard	Surround	Surround	Point	DVC	DVC	Standard	Standard	Surround	DVC	LCR
Connector Type	Gold plated push terminals												
Frequency Response	55 Hz - 20 kHz	42 Hz - 20 kHz	36 Hz - 20 kHz	42 Hz - 20 kHz	36 Hz - 20 kHz	42 Hz - 20 kHz	42 Hz - 20 kHz	36 Hz - 20 kHz	42 Hz - 20 kHz	36 Hz - 20 kHz	42 Hz - 20 kHz	42 Hz - 20 kHz	42 Hz - 20 kHz
Adjustments	Tweeter +2dB/0/-2dB	Tweeter +2dB/0/-2dB	Tweeter +2dB/0/-2dB	Surround Mode Bi/Di	Surround Mode Bi/Di	Tweeter +2dB/0/-2dB	Tweeter +2dB/0/-2dB Per Channel	Tweeter +2dB/0/-2dB Per Channel	Tweeter +2dB/0/-2dB	Tweeter +2dB/0/-2dB	Surround Mode Bi/Di	Tweeter +2dB/0/-2dB Per Channel	Dialogue Enhancement On/Off
Crossover Frequency	2.75 kHz	2.5 kHz	2.2 kHz	2.5 kHz	2.2 kHz	2.35 kHz	2.5 kHz	2.2 kHz	2.6 kHz	2.35 kHz	2.6 kHz	2.6 kHz	2.5 kHz
Nominal Impedance	8 ohm	Dual 8 ohm	Dual 8 ohm	Dual 8 ohm	8 ohm	8 ohm	Dual 8 ohm	8 ohm					
Power Peak	130 Watts												
Sensitivity	90 dB	89 dB	90 dB	89 dB	90 dB	89 dB	90 dB	91 dB	90 dB	90 dB	89 dB	90 dB	89 dB
Tweeter	3/4" Adjustable	3/4" Adjustable	1" Adjustable	3/4" Adjustable dual	1" Adjustable dual	3/4" Adjustable	3/4" Adjustable dual	1" Adjustable dual	3/4" Dual	1"	3/4" Dual	3/4" Dual	3/4" Adjustable
Woofer	4"	6"	8"	6"	8"	6"	6"	8"	6"	8"	6"	6"	6"
Mounting	Mounting Depth: 4.6" Mounting Depth w/ Enclosure: 5.9"	Mounting Depth: 4.8" Mounting Depth w/ Enclosure: 6.2"	Mounting Depth: 5.2" Mounting Depth w/ Enclosure: 6.6"	Mounting Depth: 4.8" Mounting Depth w/ Enclosure: 6.2"	Mounting Depth: 5.2" Mounting Depth w/ Enclosure: 6.6"	Mounting Depth: 5.2" Mounting Depth w/ Enclosure: 6.6"	Mounting Depth: 4.8" Mounting Depth w/ Enclosure: 6.2"	Mounting Depth: 5.2" Mounting Depth w/ Enclosure: 6.6"	Mounting Depth: 3.7" Mounting Depth w/ Enclosure: 3.8"	Mounting Depth: 3.6" Mounting Depth w/ Enclosure: 3.8"	Mounting Depth: 3.7" Mounting Depth w/ Enclosure: 3.8"	Mounting Depth: 3.7" Mounting Depth w/ Enclosure: 3.8"	Mounting Depth: 3.7" Mounting Depth w/ Enclosure: 3.8"
Dimensions (W x H x D)	Finished Dimension w/ Grill: 7.5"	Finished Dimension w/ Grill: 9.6"	Finished Dimension w/ Grill: 11"	Finished Dimension w/ Grill: 9.6"	Finished Dimension w/ Grill: 11"	Finished Dimension w/ Grill: 11"	Finished Dimension w/ Grill: 9.6"	Finished Dimension w/ Grill: 11"	Finished Dimension w/ Grill: 8.9" x 13"	Finished Dimension w/ Grill: 10.3" x 15"	Finished Dimension w/ Grill: 8.9" x 13"	Finished Dimension w/ Grill: 8.9" x 13"	Finished Dimension w/ Grill: 15.7" x 8.9"
Cutout Dimension (Diameter for IC) (Height x Width for IW)	6.2"	8.3"	9.7"	8.3"	9.7"	9.7"	8.3"	9.7"	11.7" x 7.6"	13.7" x 9"	11.7" x 7.6"	11.7" x 7.6"	7.6" x 14.4"
Weight	3.1 lb	4.7 lb	5.2 lb	4.8 lb	5.3 lb	5.2 lb	5.1 lb	5.6 lb	5.6 lb	6.0 lb	5.6 lb	5.8 lb	7.6 lbs
Dog ear clamping range	3/8" to double 1/2" substrate												
Optimal Air Volume Behind Speaker	3 ~ 5 Liters	15 ~ 20 Liters	40 ~ 45 Liters	15 ~ 20 Liters	40 ~ 45 Liters	15 ~ 20 Liters	15 ~ 20 Liters	40 ~ 45 Liters	15 ~ 20 Liters	35 ~ 40 Liters	15 ~ 20 Liters	15 ~ 20 Liters	35 ~ 40 Liters
Listening angle	120	110	110	110	110	120	110	110	100	100	110	110	100



VISIT US AT  
[episodespeakers.com](http://episodespeakers.com)