

C-GMA/GMA

15-pin HD & 3.5mm Stereo Audio Cable

| VGA/UXGA - 15-pin HD



Kramer's C-GMA/GMA is a high-performance cable with male 15-pin HD and 3.5mm stereo audio connectors at each end. It is perfect for computer graphics video to display installations that require an audio signal as well

FEATURES

Quality Construction - Constructed using our rugged and flexible 14-conductor cable Easy Connection - Pre-terminated with molded 15-pin HD connectors (male to male), gold-plated pins and thumbscrews and a 3.5mm stereo mini jack

Easy Installation - Audio leads extend 24in (61cm) beyond the 15-pin HD head at one end, and 20cm (8in) at the other

All Pins Connected for DDC2 and EDID Support

Varied Selection of Lengths - Available in versions of 3 to 75ft (0.9 to 22.9m)

Cable Specs - For detailed cable specs, see Kramer BC-3X2T7S

TECHNICAL SPECIFICATIONS

Attenuation (dB/100 -0.5dB @1MHz

-1.3dB @5MHz -1.9dB @10MHz -4.0dB @50MHz -5.7dB @100MHz

-8.0dB @180MHz -14.0dB @400MHz

Conductor:

26 AWG 7/34 tinned copper

26 AWG 7/34 tinned copper

Dielectric:

Foam polyethylene with red, green, blue color coding

0.076in (1.95mm)

Shield:

(A) 90% spiral 38 AWG tinned copper. (B) Aluminum foil/Mylar 25% overlap rate

(A) 85% braid 36 AWG tinned copper.

(B) Mylar 25% overlap rate

(A) 85% braid 36 AWG tinned copper. (B) Aluminum foil/Mylar 25% overlap rate

Inner Jacket:

PVC

Jacket Colors:

Black

White & white/black, red & red/black

Red, orange, brown, yellow, black, red/black

Center Conductor:

0.019in (0.48mm)

Individual Coax:

0.102in (2.6mm)

Impedance:

 75Ω

DC Resistance:

 45Ω per 1000ft, 148Ω per km

Capacitance:

17.3pF per foot, 57pF per meter

Temperature:

-4° to 167°F (-20° to 75°C)

Jacket:

HD polyethylene

HD polyethylene

Diameter:

0.34in (0.88mm)

0.34in (0.88mm)

Conductors:

26 AWG 7/34 tinned copper

Outer Jacket:

PVC

Outer Jacket Color:

Dark gray with white lettering

Outer Diameter:

0.393in (10.0mm)

UL:

CL2

CSA:

C(UL) CL2



CONFIGURATIONS

C-GMA/GMA-3	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-6	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-10	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-15	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-25	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-35	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-50	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-75	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable