



CP-GM/GM/xl

15-pin HD Cable with a 45° Side-Angled Connector – Plenum Rated

| VGA/UXGA - 15-pin HD



Kramer's new CP-GM/GM/xl cable offers the highest possible performance and a configuration designed to give installers and users a new level of convenience and aesthetics. It is ideal for any application requiring no-compromise quality and performance in a plenum rated VGA cable

FEATURES

Plenum Rating - CP versions of Kramer VGA cables are constructed from CL2P and CMP rated cables

High-Quality Connectors - Slim connectors with shallow depth profile are top priority in this new generation. At the same time aesthetics are even nicer than before, using elegant molded connectors at one end where it is typically connected to a projector. At the other end an extra shallow 45° VGA connector with removable metal shells is used to provide all possible options for installation in tight quarters

Quality Construction - Kramer's unique hybrid construction using molded and back shell connectors

Flexible Applications - RGBHV signals are all assigned to coaxes, making it easy to cut and convert one end to 5 BNC in the field if needed

Companion Wall Plates - Use Kramer wall plates like WP-209

Varied Selection of Lengths - Available in versions of 3 to 150ft (0.9 to 45.7m)

Cable Specs - For detailed specs, see Kramer BCP-6X2T bulk cable. Full support of DDC and pin 9

CONFIGURATIONS

CP-GM/GM/XL-3	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-6	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-10	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-15	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-25	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-35	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-50	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-75	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-100	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-125	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)
CP-GM/GM/XL-150	15-pin HD (M) to 15-pin HD (M) Molded (Straight) to Backshell (45°)