

CRS-PlugNView-H

Active Optical Armored 4K HDMI Cable



CRS-PLUGNVIEW-H cable is a high-speed HDMI active optical cable (AOC) designed with heavy-duty durability perfectly suited for the harshest use and abuse expected from rental and road applications. CRS-PlugNView-H supports resolutions up to 4K@60 (4:4:4) 18 Gbps over long cable runs up to 100 meters without the need for an external power supply or additional extenders

FEATURES

High Resolution over Long Range - Active cable supports resolutions up to 4K@60 (4:4:4) over long cable runs up to 100 meters

High Data Transfer Rate - Up to 18 Gbps

No External Power Needed - Powers the active units via the HDMI connector with a power consumption of only 0.25W:50mA @5V

Comprehensive HDMI Support - HDCP 2.2, HDR-10, HLG, Dolby Vision™, deep color, x.v.Color™, 5.1/7.1 lossless Dolby® TrueHD, DTS-HD Master Audio®, EDID and CEC

Extremely Durable - integrated. stainless steel, corrugated tube with Kevlar reinforcement protects the internal optical fibers. A TPU jacket, heavy duty connectors and robust waterproof & impact resistant connector covers ensure high pulling strength and compression load. Dispensed from a solid, mobile plastic spool

Varied Selection of Lengths - Available in versions from 10 to 100m (33 to 328ft)



TECHNICAL SPECIFICATIONS

Video Resolution: Up to 4K 60Hz 4:4:4 (3840x2160 & 4096x2160)

Data Rate: Up to 18 Gbps

Supported color spaces: RGB, YCbCr, xvYCC, Adobe sRGB, sYCC601, BT.2020

HDMI Support: HDCP 2.2, HDR-10, HLG, Dolby Vision™, EDID and CEC

Audio Supported audio formats: Dolby® Digital Plus, Dolby® TrueHD, DTS-HD Master

Audio®, DVD Audio, SA-CD

PHYSICAL Connector-1 (source end): Male HDMI Type A, 24K gold-plated

Connector-1 (display end): Male HDMI Type A, 24K gold-plated

HDMI Connector Dimensions: 27.8"x 0.78"x 0.38" (70.7mm x 20mm x 9.8mm)

Cable Structure: Hybrid Optical Fiber Cable

Fiber Optic: 50/125u OM3 fiber

Armor Material: Kevlar® and stainless steel

Long term crush resistance: 1000N (100 kg, 225lbs)

Short term crush resistance: 2000N (204 kg, 450lbs)

Bending radius: 10 D (Dynamic) / 20 D (Static)

Long term tensile strength test: 400N (41 kg, 90lbs)

Short term tensile strength test: 800N (81 kg, 180lbs)

Connector bending test > 10000 cycles:

JACKET Material: TPU (thermoplastic polyurethane) - LSHF

Color: Black

Diameter: 5.8mm

Power Source: No external power supply is needed (draws current from the video source)

Consumption 0.25W max.:

Environmental Conditions

Environmental Specification:

Operating Temperature: +32~+122°F (0~+50°C)

Storage Temperature: -40~+158°F (-40~+70°C)

Operating Humidity: 10 ~ 80%

Regulatory:

REGULATORY Environmental: CE, FCC

Safety: RoHS 2011/65/ EU

Product Dimensions 24.00cm x 20.00cm x 32.00cm (9.45" x 7.87" x 12.60") W, D, H

Product Weight 5.2kg (11.5lbs) approx

Shipping Dimensions $38.50cm \times 26.50cm \times 47.00cm (15.16" \times 10.43" \times 18.50")$ W, D, H

Shipping Weight 6.3kg (13.9lbs) approx





CONFIGURATIONS

CRS-PlugNView-H-33	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-50	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-66	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-98	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H- 131	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H- 164	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H- 197	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H- 230	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H- 262	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H- 328	Active Optical Armored 4K HDMI Cable