

CEILING SPEAKER

CS-05F/610F/615F/620FH/630FH/680FH



FEATURES

CS-05F/610F/615F

- Contains a premium grade speaker unit
- Best reliability
- The beautiful and graceful cabinet design
- Easy installing and convenience
- Full Range of 1 way speaker system (6.5" unit)
- Multi-tap switch offers an easy way to change taps on a transformer(CS-610F/615F)

CS-620FH/630FH/680FH

- Contains a premium grade speaker unit
- Best reliability
- The beautiful and graceful cabinet design
- Easy installing and convenience
- 2 Way speaker system (6.5" -2way coaxial type)
- Multi-tap switch offers an easy way to change taps on a transformer


SPECIFICATIONS

Model		CS-05F	CS-610F	CS-615F	CS-620FH	CS-630FH	CS-680FH
Unit		6.5"					
Power Handling (AES)		5W	10W	15W	20W	30W	80W
Input Power	100V	5W/3W/1W	10W/5W/3W	15W/7.5W/4W	20W/10W/5W	30W/20W/10W	80W/40W/20W
	70V	-	-	-	-	-	-
Impedance	100V	2kΩ/3.3kΩ/10kΩ	1kΩ/2kΩ/3.3kΩ	660Ω/1.3kΩ/2.6kΩ	500Ω/1kΩ/2kΩ	330Ω/500Ω/1kΩ	125Ω/250Ω/500Ω
	70V	-	-	-	-	-	-
	LOW	-	-	-	-	8Ω	-
Frequency Range (-20%)		95Hz ~ 18.4kHz	100Hz ~ 19.4kHz	105Hz ~ 18kHz	100Hz ~ 20kHz	85Hz ~ 20kHz	100Hz ~ 20kHz
Sensitivity (1W/1m)		86dB	89dB	89dB	86dB	86dB	88dB
Maximum SPL [Cont]		93dB	99dB	101dB	99dB	101dB	107dB
Nominal Dispersion (HxV)	1kHz	192°	188°	192°	184°	126°	248°
	4kHz	61°	62°	64°	92°	59°	72°
Weight (Net)		0.65kg / 1.43lb	0.85kg / 1.87lb	0.88kg / 1.94lb	2.00kg / 4.4lb	2.00kg / 4.4lb	3.40kg / 7.4lb
Dimensions (Net, WxD)		230(Φ) x 100(D)mm / 9(Φ) x 4(D)in			230(Φ) x 168(D)mm / 9(Φ) x 6.6(D)in		


* Design and specification are subject to be changed for the improvement of product quality without pre notice.

FREQUENCY RESPONSE


► CS-05F




► CS-610F




► CS-615F




► CS-620FH



► CS-630FH





► CS-680FH



CS-05F/610F/615F/620FH/630FH/680FH


Inserting Speaker Into Ceiling

► CS-05F/610F/615F




Ceiling Speaker Part-List/Inserting Speaker Into Ceiling


► CS-620FH/630FH/680FH



5	SCREW 1WPTC 4 x 12B	2
4	BKT-RING	1
3	BKT-RAIL	2
2	SET	1
1	GRILL COVER	1
NO	NAME	QTY




※ Ceiling Hole Size : Ø200~Ø205



1. Turn clockwise and fit carefully until approaching ceiling or BKT-RING.
2. Put GRILL-COVER on the hall of SET and press to be combined.

INPUT TERMINAL


► CS-05F



► CS-610F/615F


COM(-) BLACK
(+) RED

► CS-620FH/630FH/680FH




OUTPUT TERMINAL

► CS-610F




PA SPEAKER 10W / 5W / 3W
The impedance switch selects a different range of values on a transformer

► CS-615F




PA SPEAKER 15W / 7.5W / 3.8W
The impedance switch selects a different range of values on a transformer

► CS-620FH




PA SPEAKER 5W / 10W / 20W
The impedance switch selects a different range of values on a transformer

► CS-630FH



PA SPEAKER 10W / 20W / 30W
The impedance switch selects a different range of values on a transformer

► CS-680FH



PA SPEAKER 20W / 40W / 80W
The impedance switch selects a different range of values on a transformer

Inter-M Corporation

- Office : 719, DOBONG-RO, DOBONG-GU, SEOUL, KOREA
- Tel : +82-2-2289-8140~8, Fax : +82-2-2289-8149
- Home page: <http://www.inter-m.com>, E-mail: overseas@inter-m.com

Inter-M Corp. (IMA)

- Office : 5666 CORPORATE AVE. CYPRESS, CA 90630
- Tel : +1-714-828-2200, Fax : +1-714-828-2210
- E-mail : info@inter-m.net, Home Page : www.inter-m.net