

A Hardy Mini Dome

Visualint™ 2MP IP Dome Outdoor Camera with Starlight + Virtual Technician

This outdoor-rated IR dome camera was designed for a variety of applications, and features Visualint's premium Starlight low-light color sensor so you can see clearly in the dark. Constructed using glass lenses and heavy-duty metal housing, it stays hardy in any environment.



VI-3000-DOM-S-WH

Key Features



Embedded Intelligent Analytics



Professional Video Monitoring




Enhanced Control & Integration

Without Starlight




With Starlight



Starlight Low-Light Color Sensor

2MP



Widescreen & High Definition

Product Details

Technical Specs & Features	VI-3000-DOM-S-WH
Audio Inputs / Outputs	1-ch / None
Image Sensor	2MP 1/2.8" Starlight CMOS
Maximum Record Resolution	1920 × 1080
Lens	2.8mm, F1.3
Est. Horizontal Viewing Angle	108.7°
Minimum Illumination	Color: 0.002Lux (F1.2,AGC ON) Black&White: 0.001Lux (F1.2,AGC ON) 0 Lux with IR
IR Range	65 ft
Remote Monitoring Integration	Immix
Recording Trigger	No
Full Screen Monitoring	Yes
Image Snapshot	Yes
Audio Support	1-ch, G.711A/G.711U/ADPCM/AAC
Triggered Action Desc.	Email, HTTP Notification, FTP
SD Card Support	N/A
Network / Ethernet Desc.	10M/100M Ethernet Interface
Supported Network Protocols	TCP, UDP, HTTP, MULTICAST, UPnP, DHCP, PPPoE, DDNS, NFS, FTP, NTP, RTP, RTSP, IPv6, SNMP, SMTP
Power Consumption	DC12 V, PoE (802.3af), 2W (IR OFF), 4W (IR ON)
Color	White
Dimensions (W x H x D)	4.8" x 3.6" x 4.8"
Weather Rating	IP66
Certifications	CE, FCC
Operating Temperature	-20-140°F, 0~95% RHG
Weight	1 lb

Short-Range IR



Multiple Video and Snapshot Streams

