



5" DIRECTOR MODELS

Designed with Architects and Interior Designers in mind, the Director 5" Series aesthetically matches high-end 6" can lights. That doesn't mean we've sacrificed the audio quality. Paired with our matching 5" aperture in-ceiling sub and DSP3-100 Amplifier, looking good had never sounded better.



D59



D57



D57DT

DETAILS MATTER

■ Multi-Motion™ Tweeter

The entire tweeter pivots allowing the sound to be directed toward the listening area from anywhere in the room.

■ DPSD™ Tweeter

This patented tweeter has the greatest output and is able to crossover much lower to either the woofer or the midrange improving both dispersion and the frequency response.

■ Compression Molded Baskets

These complex baskets that support the woofer cones were computer designed and compression molded with absolute precision allowing for unique support and venting elements to assure peak performance.

■ Tool-Less Mounting System

The Tool-Less Installation secures the speaker in the ceiling with the exact torque to ensure a tight fit. This is accomplished by squeezing the clips into place and locking the speaker with a twist.

■ X-Wave™ Woofer Surround

This suspension element absorbs unwanted frequencies that reflect up and down the woofer cone to reduce harmonic distortion while maintaining the desired linear travel of the woofer.

SPECIFICATIONS

MODEL	D59	D57	D57DT/SUR
PART	SCD50900	SCD50700	SCD2T50700
Woofers	5 1/4" Kevlar®	5 1/4" Glass Fiber	5 1/4" Glass Fiber
Tweeter	1" Silk DPSD™ MMP™	1" Silk DPSD™ MMP™	3/4" Dual Silk DPSD™
Power RMS	40 Watts	40 Watts	40 Watts
Power Peak	125 Watts	125 Watts	125 Watts
Frequency Response	68Hz-20kHz	69Hz-20kHz	69Hz-20kHz
Impedance	6 ohm	6 ohm	6 ohm
Diameter	6 25/32" (172mm)	6 25/32" (172mm)	6 25/32" (172mm)
Cutout Diameter	5 7/8" (149mm)	5 7/8" (149mm)	5 7/8" (149mm)
Grille Diameter	7 3/16" (183mm)	7 3/16" (183mm)	7 3/16" (183mm)
Mounting Depth	3 3/4" (95mm)	3 3/4" (95mm)	3 3/4" (95mm)

