



ECS-200-IC-8

Designed for Versatility

With flying leads for .5W, 1W, 2W, and 4W tap settings, this speaker's output can be adjusted to meet any application's requirements.

Engineered for Strength

The included tile bridge features strengthening ribs and wire loops for added support to ensure a secure installation.

Constructed for Durability

A sturdy aluminum baffle makes this speaker less prone to rust and increases durability – an ideal combination for commercial applications.

Specifications

Driver:	8" Treated Paper Cone
Voice Coil Size	1"
Dispersion Angle:	100°
Transformer Tap Settings:	.5W, 1W, 2W, 4W
Frequency Response (-6dB):	70Hz - 17KHz
Cutout Size:	10 ³ / ₄ "
Baffle Diameter:	12 ⁹ / ₁₆ "
Magnet Weight:	10 oz.
Sensitivity -2.83 v / 1 Meter:	95db
Color:	White
Baffle Material:	Powder Coated Aluminum
Connector Type:	Flying Leads
Mounting Depth:	2 ⁵ / ₈ "

Lifetime Limited Warranty

All Episode Speakers have a Lifetime Limited Warranty. This warranty includes parts and labor repairs on all components found to be defective in material or workmanship under normal conditions of use. This warranty shall not apply to products which have been abused, modified or disassembled. Products to be repaired under this warranty must be returned to SnapAV or a designated service center with prior notification and an assigned return authorization number (RA).