



ECS-250-IC-6

Engineered for Performance

The speakers' dispersion angle of 110 degrees effectively reduces hot spotting for a more uniform distribution. This provides greater flexibility in speaker spacing, because fewer speakers are required to cover the same amount of square footage.

Built for Sound

A two-way design delivers high sound quality, while Nomex spiders and high-temp voice coils ensure longevity, and a fluid-cooled neodymium tweeter delivers smooth, high-frequency performance.

Designed for Versatility

A paintable grille and baffle allows custom color matching for any commercial application.

Specifications

Woofer:	6½" Treated Paper Cone, Nomex Spider & High Temp Voice Coil
Tweeter:	1/2" Fabric Dome, Neodymium Motor, Ferrofluid Cooled
Power Handling:	50 Watts RMS, 125 Watt Peak
Dispersion Angle:	110 degrees
Transformer Tap Settings:	0.5W, 1W, 2W, 4W
Frequency Response (-6dB):	58Hz - 20KHz
Sensitivity -2.83 V / 1 Meter:	87
Adjustments:	N/A
Color:	White
Crossover Frequency:	4.3 kHz
Connector Type:	Flying Leads
Weight:	2.1 lbs. each
Grill Type:	Aluminum Micro-Perf Mesh
Cutout Dimensions:	7.7" diameter
Mounting Depth:	3.4"
Finished Dimensions:	8.5" diameter, 3" D

Lifetime Limited Warranty

All Episode Speakers have a Lifetime Limited Warranty. This warranty includes parts and labor repairs on all components found to be defective in material or workmanship under normal conditions of use. This warranty shall not apply to products which have been abused, modified or disassembled. Products to be repaired under this warranty must be returned to SnapAV or a designated service center with prior notification and an assigned return authorization number (RA).