



# HAC335-FD4



## FEATURES

### IVMS HD-TVI 3MP EXIR Turret Camera

- 3MP Video Output
- HDTVI Technology
- OSD menu, DNR
- 120 ft IR distance
- IP66 weatherproof
- Up the Coax(via coaxial cable)
- True WDR

| Specifications    |                                                  |
|-------------------|--------------------------------------------------|
| Model Number      | HAC335-FD4                                       |
| Image Sensor      | 3MP CMOS                                         |
| Video Format      | PAL / NTSC                                       |
| Effective Pixels  | 2052(H)*1536(V)                                  |
| Min. Illumination | 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR         |
| Shutter Time      | 1/30s to 1/50,000 s                              |
| Lens              | 3.6 mm(2.8mm optional)                           |
| Angle Adjustment  | Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360° |
| Day & Night       | ICR                                              |
| Video Frame Rate  | 2052*1536 @ 18fps                                |
| HD Video Output   | 1 HD-TVI output up to 1200ft with RG59U 95%      |
| CVBS Output       | N/A                                              |

| Specifications                 |                                                                           |
|--------------------------------|---------------------------------------------------------------------------|
| D/N Mode                       | Color / BW / Smart                                                        |
| Function                       | WDR, DNR, Mirror, Smart IR                                                |
| WDR                            | 120dB True WDR                                                            |
| Working Temperature / Humidity | -40 °C - 60 °C (-40 °F - 140 °F)<br>Humidity 90% or less (non-condensing) |
| Power Supply                   | 12 VDC±15%                                                                |
| Power Consumption              | Max. 5W                                                                   |
| Weather Proof Ratings          | IP66                                                                      |
| IR Range                       | Up to 120 ft                                                              |
| Communication                  | OSD (UTC Control) via DVR                                                 |
| Dimensions                     | Ø4.33"x3.67"                                                              |
| Weight                         | 0.77lbs                                                                   |
| Electrical Box                 | HTH-285ZJ-M                                                               |
| Wall Mount                     | HTH-273ZJ-130B-TRL                                                        |
| Pole Mount                     | HTH-275ZJ                                                                 |
| Corner Mount                   | HTH-276ZJ                                                                 |