



# HAC335-OD



## FEATURES

### IVMS HD-TVI 3MP Exterior IR Dome Camera

- 3MP Video Output
- HD-TVI Technology
- OSD menu, DNR
- 60 ft IR distance
- IP66 weatherproof
- Up the Coax (control over coax)
- True WDR

| Specifications    |                                                                                     |
|-------------------|-------------------------------------------------------------------------------------|
| Model Number      | HAC335-OD                                                                           |
| Image Sensor      | 3MP CMOS                                                                            |
| Video Format      | PAL / NTSC                                                                          |
| Effective Pixels  | 2052(H)*1536(V)                                                                     |
| Min. Illumination | 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR                                            |
| Shutter Time      | 1/30s to 1/50,000 s                                                                 |
| Lens              | 3.6mm (2.8mm, 6mm optional), Angle of View: 80.9°(3.6mm), 103.5°(2.8mm), 54.3°(6mm) |
| Angle Adjustment  | Pan: 0 - 360°, Tilt: 0 - 80°                                                        |
| Day & Night       | ICR                                                                                 |
| Video Frame Rate  | 1920 x 1536 @ 18fps                                                                 |
| HD Video Output   | 1 HD-TVI output up to 1200ft with RG59U 95%                                         |
| CVBS Output       | N/A                                                                                 |

| Specifications                 |                                                                        |
|--------------------------------|------------------------------------------------------------------------|
| AGC                            | support                                                                |
| D/N Mode                       | Color / BW / Smart                                                     |
| WDR                            | 120dB True WDR                                                         |
| Working Temperature / Humidity | -40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing) |
| Power Supply                   | 12 VDC±15%                                                             |
| Power Consumption              | Max. 5W                                                                |
| Weather Proof Ratings          | IP66, IK10                                                             |
| IR Range                       | Up to 60 ft                                                            |
| Communication                  | OSD (UTC Control) via DVR                                              |
| Dimensions                     | Ø4.37"x3.24"                                                           |
| Weight                         | 0.77lbs                                                                |
| Electrical Box                 | HTH-280ZJ-DM18                                                         |
| Wall Mount                     | HTH-258ZJ, HTH-272ZJ-110B                                              |
| Pendant                        | HTH-271ZJ-110                                                          |
| Pole Mount                     | HTH-275ZJ                                                              |
| Corner Mount                   | HTH-276ZJ                                                              |