

HARA05-16



FEATURES

16 Channel, 2MP TVI & Analog + Up to 32 Ch. IP Hybrid DVR

- 260 Mbps bit rate input max for IP cameras
- H.264+ video compression
- 1080p resolution real-time recording
- Third-party network cameras supported
- Up to 6 Megapixels resolution recording
- HDMI and VGA output up to 1080P
- 16 Ch. synchronous playback
- Dual Gigabit network interfaces
- ONVIF compliant

| Specifications | |
|--------------------------------|----------------------------|
| Model Number | HARA05-16 |
| Video Compression | H.264 / H.264+ |
| IP Video Input | Up to 32 Ch. (Up to 6MP) |
| Video Output | 1 HDMI, 1 VGA, 1 BNC |
| Analog Video Input | 16 |
| Incoming Bandwidth | 260Mbps |
| Audio Input/output | 16/2 |
| Two-way Audio | 1/1 |
| Real-time recording resolution | 30fps @ Up to 6 Megapixels |
| HDMI Output Resolution | 1080P 60Hz |
| VGA Output Resolution | 1080P, 60Hz |

| Specifications | |
|-----------------------|---|
| Synchronous Playback | 16 Ch. @ 1080p |
| Alarm Input/ Output | 16/4 |
| Network Interface | 2 RJ45 10M/100M/1000M adaptive Ethernet Interface |
| RAID | 0, 1, 5, 10 |
| HDD Interface | 8 SATA interfaces(up to 6TB each) |
| eSATA | 1 eSATA |
| Serial Interface | RS-232, RS-485, Keyboard |
| USB interface | 3 x USB 2.0 |
| Chassis | 19-inch rack-mounted 2U |
| Power Supply | 100~240VAC, 65W |
| Power Consumption | Max 65W. (without HDD) |
| Dimensions | 17.5"W x 18.5"D x 3.5"H |
| Weight | 17.64 lbs (without hard disk) |