



HNC328-VDZ



FEATURES

8MP VF IR Motorized Zoom, Vandal-Proof Dome With Audio, Exterior

- Full HD 1080p real-time video
- 8Megapixel (3840 x 2160) Resolution
- IR LEDs: up to 90ft
- Supports H.265
- Support onboard storage (up to 128GB)
- IP67 & IK10
- Vandal-proof
- Motorized Zoom

Specifications	
Model Number	HNC328-VDZ
Image Sensor	1/2.5" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8 ~ 12mm @ F1.4, Angle of view: 88° ~ 29°
Day & night	ICR
digital noise reduction	3D DNR
Wide Dynamic Range	120dB
Angel adjustment	Pan: 0° ~ 355°, tilt 0° ~ 75°
Video compression	H.264 / MJPEG / H.264+ / H.265 / H.265+
Max. image resolution	3840 x 2160
Frame rate	15fps (3840×2160), 30fps (2944×1656)

Specifications	
Audio	1/1
Network storage	NAS
Alarm	1/1
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark, dual stream
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Onboard storage	Built-in Micro SD slot, up to 128 GB
Onboard Reset	Yes
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max. 11.5W
Impact protection	IK10
Ingress protection level	IP67
IR range	Up to 90ft
Dimensions	Ø 6.04" x 5.24"
Weight	2.84 lbs.
Electrical Box	N/A (built in with camera)
Recess Mount	N/A
Wall Mount	HTH-473ZJ-155
Pendant Mount	HTH-471ZJ-155
Pole and Corner Mount	P:HTH-475ZJ-SUS, C:HTH-476ZJ-SUS