



PURPOSE AV - 8MP, EXIR TURRET, OUTDOOR, 2.8MM

SKU: HNC328-XDU

FEATURES

- » 8 MP (3840 x 2160) resolution
- » Full HD 4 MP real-time video
- » True WDR and 3D DNR and BLC
- » EXIR illuminator up to 100 ft
- » IP67
- » PoE
- » Comparable to DS-2CD2383G0-IU

SPECIFICATIONS:

Туре	EXIR, Exterior
Image Sensor	1/2.5 Inch Progressive Scan CMOS
Lens	2.8 mm at F1.6
Field of View	102 deg
Minimum Illumination	0.01 lux at F1.2 (AGC On), 0 lux with IR
Effective Pixels (H x V)	3840 x 2160
Video Compression	H.264/H.264+/H.265/H.265+/MJPEG
Alarm Trigger	Motion Detection, Tampering Alarm
Frame Rate	15 fps (3840 x 2160), 30 fps (2560 x 1440)
Shutter Speed	1/3 - 1/100000 sec
Speco DNR	3D DNR
Wide Dynamic Range	True WDR, 120 dB
Audio	1 In/0 Out, Built-In Mic
Supported Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPOE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, QoS
Functions	User Authentication, Watermark
IR Range	Up to 100 ft
Mounting Type	Electrical Box/Wall/Pole/Corner
Angle Adjustment	Pan: 0 - 360 deg, Tilt: 0 - 75 deg, Rotation: 0 - 360 deg
Streams	Dual
Communication Interface	(1) RJ-45 10M/100M Ethernet Port
Enclosure Rating	IP66
Image Settings	Saturation, Brightness, Contrast, Sharp- ness Adjustable Through Client Software or Web Browser
Network Storage	NAS
Bit Rate	32 kbps - 16 Mbps
System Compatibility	ONVIF, PSIA, CGI
Power Supply	12 VDC +/-10%, PoE (802.3af)
Power Consumption	5 W Maximum (7 W with ICR On)
Temperature Rating	-22 to 140 deg F
Relative Humidity	95% or Less (Non-Condensing)
Dimensions	5 Inch Dia x 3.8 Inch H
Weight	1.5 lb











