



HNC6924F-A



FEATURES

EXIR Flexible PanoVu Network Camera

- 30fps @ 1920 x 1080
- H.265, H.265+, H.264, H.264+
- 30 to 90ft IR Range
- IP67, IK10
- 4 Flexible Lens
- 6 behavior analysis, 4 exception detection, and face detection

Specifications	
Model Number	HNC6924F-A
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.003 Lux @ F1.2, 0 Lux with IR
Shutter Speed	1/25s - 1/100,000s
Day & Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	DWDR
2-Axis Adjustment	Pan: 0° to 355°, tilt: 0° to 90°
Lens	4 x 6mm lens
Aperture	F2.0
FOV	Horizontal field of view: 180°, Vertical field of view: 30.3°
IR Range	4 x IR LEDs, up to 60ft.
Wave Length	850nm

Specifications	
Video Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Video Bit Rate	32 Kbps to 16 Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM/AAC
Audio Bit Rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
Behavior Analysis	Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection
Max. Resolution	7008 × 1080
Frame Rate	30fps @ 7008 x 1080
Audio I/O	1/1
Alarm I/O	1/1
On Board Storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
Communication Interface	1 RJ45 10M/100M/1000M Ethernet port 1 RS-485 interface (-S)
Fiber optic interface	FC interface
Protection Level	IP67
Power Supply	12 VDC ± 20%, three-core terminal block, PoE: 802.3at, class 4
Power Consumption	Max. 18W
Working Temperature	-40°C to 60°C (-40°F to 140°F)
Dimensions	7.5" × 8.2" x 8.2"
Weight	7.7lbs
Wall Mount	HTH-602ZJ
Pendant Mount	HTH-661ZJ
Pole Mount	HTH-602ZJ-Pole
Corner	HTH-602ZJ-Corner