



ROCK SPEAKER COLLECTION

When a natural aesthetic is required, there is nothing like a rock speaker to fit the bill. Using a polyurethane/resin composite that is incredibly durable, the stone-like exterior will survive the harshest environments and provide quality sound for years to come. Available in 6" and 8" two-way designs and offering an additional 8" subwoofer, these speakers can stand on their own or be mixed with the rest of the Seasons Collections as the application demands.

The 70V/8 ohm Rock speakers feature multiple taps off the transformer adjusted by a rotary switch on the bottom side of the speaker.



OSR85

Part: OSR8500
Woofer: 8" Injection Polypropylene with Rubber Surround
Tweeter: 1" Titanium
Power RMS: 50 Watts
Power Peak: 100 Watts
Frequency Response: 40Hz – 20kHz
Impedance: 8 ohm,
70v – 60W/30W/15W/7.5W
transformer taps
Dimensions: 15 x 21 x 16" (38 x 52 x 39 cm)
Weight: 11 lbs (5 kg)
Environment Temp: -22° to 158° F
(-30° to 70° C)



OSR65

Part: OSR6500
Woofer: 6" Injection Polypropylene with Rubber Surround
Tweeter: 1" Titanium
Power RMS: 50 Watts
Power Peak: 100 Watts
Frequency Response: 50Hz – 20kHz
Impedance: 8 ohm,
70v – 30W/15W/7.5W/3.7W
transformer taps
Dimensions: 12 x 17 x 14" (29 x 43 x 35 cm)
Weight: 11 lbs (5 kg)
Environment Temp: -22° to 158° F
(-30° to 70° C)



OSR8SUB

Part: OSR800SUB
Woofer: 6" Injection Polypropylene with Rubber Surround
Power RMS: 60 Watts
Power Peak: 120 Watts
Frequency Response: 35Hz – 150kHz
Impedance: 8 ohm,
70v – 30W/15W/7.5W/3.7W
transformer taps
Dimensions: 15 x 21 x 16"
(38 x 52 x 39 cm)
Weight: 22 lbs (10 kg)
Environment Temp: -22° to 158° F
(-30° to 70° C)