



TBUS-202xl

Dual Pop-Up Table Mount Multi-Connection
Solution

| VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45



Kramer's TBUS-202xl provides an extremely simple, affordable and elegant single-push dual pop-up multi-connection boardroom solution. By pressing down gently on the lid, the unit opens and closes pneumatically. TBUS-202xl is fast and easy to install and flexible to configure. It opens facing both sides of the table making it ideal for any meeting room

FEATURES

Pneumatic Lift - Easy opening & closing by pressing down gently on the covers. When not in use, they lower flush with the table

Power Input - Universal, USA, European and many other worldwide power sockets available. Power socket modules are purchased separately

4 Fixed Inputs per Connecting Surface - 15-pin HD, HDMI, 3.5mm & Ethernet

Elegant and Rugged Rectangular Design - The sturdy and attractive anodized aluminum enclosure provides maximum connectivity in the smallest possible footprint, and at the same time is cost effective and easy to install

Installation Requirements - Requires tools and expertise to cut a 267mm x 122mm (10.5" x 4.8") rectangular hole in the surface of the furniture. Maximum table thickness is 76mm (3")



KRAMER

TECHNICAL SPECIFICATIONS

PORTS:	2 connecting surfaces, each with 1 HDMI connector, 1 Ethernet RJ-45 connector, 1 15-pin HD connector, 1 3.5mm mini jack
POWER SOCKET ASSEMBLIES:	USA Universal 100-240V AC, 50/60Hz, 5A per outlet; 100-220V AC, 50/60Hz, 5A per outlet; Germany and EU 100-240V AC, 50/60Hz, 5A per outlet; Belgium and France 100-240V AC, 50/60Hz, 5A per outlet; Italy 100-240V AC, 50/60Hz, 5A per outlet; Australia 100-240V AC, 50/60Hz, 5A per outlet; Israel 220V AC, 50/60Hz, 5A per outlet; South Africa 220V AC, 50/60Hz, 5A per outlet; Switzerland 220V AC, 50/60Hz, 5A per outlet; UK 220V AC, 50/60Hz, 5A per outlet; Brazil 220V AC, 50/60Hz, 5A per outlet
FUSE RATING:	T 6.3A 250V
OPERATING TEMPERATURE RANGE:	+5° to +45°C (41° to 113°F)
OPERATING HUMIDITY RANGE:	10 to 90% RHL, non-condensing
STORAGE TEMPERATURE RANGE:	-20° to +70°C (-4° to 158°F)
STORAGE HUMIDITY RANGE:	5 to 95% RHL, non-condensing
INCLUDED ACCESSORIES:	Cut out metal template
COLOR:	Black and silver sandblasted finish
OPTIONS:	Power socket kits, power cord
Product Dimensions	28.50cm x 14.00cm x 16.00cm (11.22" x 5.51" x 6.30") W, D, H
Product Weight	1.8kg (3.9lbs) approx
Shipping Dimensions	44.50cm x 35.00cm x 42.50cm (17.52" x 13.78" x 16.73") W, D, H
Shipping Weight	2.5kg (5.5lbs) approx





KRAMER

CONFIGURATIONS

TBUS-202XL(B)	Enclosure - Black Sand Blasted Anodized Aluminum Top
---------------	--

TBUS-202XL(BC)	Enclosure - Silver Sand Blasted Anodized Aluminum Top
----------------	---
