



## VGAA-OUT2-F16

2-Channel VGA with Analog Audio Output  
Card

| Kramer Core



VGAA-OUT2-F16 is a two-channel VGA with analog audio output card for the VS-1616 Series Modular Multi-Format Digital Matrix Switchers. The VGAA-OUT2-F16 outputs two VGA with analog audio signals from the chassis. Audio output is accessed by connecting the supplied Kramer VGA with audio cables to each VGA port

### FEATURES

- Max. Bandwidth - 450MHz
- HDTV Compatible
- Analog Audio Over Breakaway Connector



# KRAMER

## TECHNICAL SPECIFICATIONS

---

PORTS:	2 VGA on 15-pin HD connectors, 2 unbalanced analog audio on 3.5mm mini jack connectors (accessible via C-GF/GMAF-30 cables)
BANDWIDTH:	450MHz
MAXIMUM RANGE:	10m (32ft)
POWER CONSUMPTION:	5.5W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE
INCLUDED ACCESSORIES:	2 C-GF/GMAF-30 cables
Product Dimensions	19.00cm x 13.00cm x 2.00cm (7.48" x 5.12" x 0.79" ) W, D, H
Product Weight	0.1kg (0.3lbs) approx
Shipping Dimensions	27.00cm x 23.20cm x 5.60cm (10.63" x 9.13" x 2.20" ) W, D, H
Shipping Weight	0.6kg (1.2lbs) approx