

## **VM-22H**

2x1:2 Compact HDMI Switchable DA

| HDMI | HDCP Compliant





The VM-22H is a distribution amplifier for HDMI signals. The unit reclocks and equalizes one of two selectable input signals and distributes it to two identical outputs

## **FEATURES**

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)

**HDCP** Compliant

HDMI Support - Deep Color, x.v.Color™, Lip Sync, CEC

3D Pass-Through

EDID Pass-through - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

Active Output LED Indicators

Control - Front panel or IR remote switching

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances

Compact DigiTOOLS® - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



## **TECHNICAL SPECIFICATIONS**

INPUTS: 2 HDMI connectors

**OUTPUTS**: 2 HDMI connectors

BANDWIDTH: 6.75Gbps (2.25Gbps per graphic channel)

**HDMI STANDARD:** 

COMPLIANCE WITH Supports HDMI and HDCP

CONTROLS: EDID SETUP button, input select button, IR

INDICATOR LEDs: IN 1, IN 2, OUT 1, OUT 2, and ON LEDs

POWER

CONSUMPTION:

5V DC, 910mA

**INCLUDED** ACCESSORIES: Power supply, bracket installation kit, IR remote control (upon request)

**OPTIONS:** HDMI/HDMI male-to-male cables

**Product Dimensions** 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

**Product Weight** 0.3kg (0.7lbs) approx

Shipping Dimensions 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

Shipping Weight 0.6kg (1.2lbs) approx



