

VP-510 4K to 2K Down-Converter

| HDMI | 4K/30 UHD



VP-510 is a down-converter for 4K UHD HDMI signals. The unit takes a 4K resolution input, provides a loop output and down-converts it to 2K resolution. It allows the use of legacy equipment with 4K signals (23.98Hz to 30Hz)

FEATURES

HDMI Signal Downscaling - From 4K UHD to 2K/1080p

Resolution Support - 4K@24Hz 4096×2160p and 4K@24/25/30Hz 3840×2160p

HDMI Signal Bypass - For non-4K resolutions

HDMI Looping Input

Max. Data Rate - 10.2Gbps (3.4Gbps per graphic channel)

HDMI Support - 3D, Deep Color, x.v.Color™, Dolby® TrueHD, Dolby Digital Plus, DTS-HD® and 7.1

PCM



TECHNICAL SPECIFICATIONS

INPUTS: 1 HDMI (looping) on an HDMI connector

OUTPUTS: 1 HDMI and 1 loop on HDMI connectors

PORT: 1 mini-USB for firmware upgrading

MAX. DATA RATE: 10.2Gbps (3.4Gbps per graphic channel)

INDICATOR LEDS: ON, BYPASS, 4K IN, OUTPUT CONNECTED

SUPPORTED Up to HDCP 1.4

STANDARDS:

SUPPORTED 4K 3840x2160 @23.98/24Hz (HDMI_VIC 3), 3840x2160 @25Hz (HDMI_VIC 2), **RESOLUTIONS:** 3840x2160 @29.97/30Hz (HDMI_VIC 1), 4096x2160 @23.98/24Hz (HDMI_VIC 4)

POWER 5V DC, 550mA

CONSUMPTION:

OPERATING TEMPERATURE: 0° to +40°C (32° to 104°F)

STORAGE

 -40° to $+70^{\circ}$ C (-40° to 158° F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

INCLUDED

ACCESSORIES:

Power supply

Product Dimensions 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

Product Weight 0.2kg (0.4lbs) approx

Shipping Dimensions 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

Shipping Weight 0.5kg (1.1lbs) approx



