

VS-211HDxI

2x1:2 SDI Auto Switcher

| 3G HD-SDI - BNC



The VS-211HDxl is a high-performance automatic switcher for 3G HD-SDI video signals. When configured as a standby switcher, it switches to the secondary input when the primary input is lost

## **FEATURES**

Max. Data Rate - 3Gbps

Multi-Standard Operation - SDI (SMPTE 259M and SMPTE 344M), HD-SDI (SMPTE 292M) & 3G HD-SDI (SMPTE 424M)

**HDTV** Compatible

Control - Contact closure or automatic switching

Automatic Standby Switching - Switches from the secondary input to the primary input when a primary signal is detected

Primary Input - Selectable

Active Input LED Indicators

Compact DigiTOOLS  $^{\text{TM}}$  - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



## TECHNICAL SPECIFICATIONS

INPUTS: 2 SD/HD/3G HD-SDI video on BNC connectors

OUTPUTS: 2 SD/HD/3G HD-SDI video on BNC connectors

MAX. OUTPUT

LEVEL:

 $800 \text{mVpp}/75\Omega$ 

DATA RATE: Up to 2.97Gbps

CONTROLS: Contact closure remote control, input default selection switch

COUPLING: AC

POWER 5V DC, 400mA

CONSUMPTION:

INCLUDED ACCESSORIES:

Power supply, mounting bracket

Product Dimensions 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

Product Weight 0.2kg (0.4lbs) approx

Shipping Dimensions  $23.20cm \times 12.00cm \times 8.90cm (9.13" \times 4.72" \times 3.50") W, D, H$ 

Shipping Weight 0.6kg (1.3lbs) approx

