

# CRS-AOCH/XL

## Rental & Staging Active Optical Pluggable HDMI Cable

Kramer's CRS-AOCH/XL is an Active Optical HDMI Cable for running 4K@60Hz 4:2:0 UHD, 4K@30Hz 4:4:4, over longer distances up to 100 meter(328 ft), in a simple & practical way.

The CRS-AOCH/XL cables are specially designed to not only meet the demanding conditions of day to day installations, but were also made to withstand the toughest of conditions in the rental, staging and production markets. Constructed with a TPU (Thermoplastic Polyurethane) rated jacket which has excellent abrasion resistance, tensile strength and high tear resistance, while still thinner, lighter and more flexible than copper cables while providing transparent EDID and HDCP support without signal attenuation and also provide reduced risk of EMI and RFI interference which provides a perfect solution for critical AV installations that demand the highest signal integrity.



Non-slip connection with 15lbs of restraining force


### Features

- Video Resolution – 4K@60Hz 4:2:0 UHD, 4K@30Hz 4:4:4 8Bit, full HD, 3D Deep Color across all lengths
- High Data Transfer Rate – Up to 10.2Gbps
- Embedded Audio – PCM 8-channel, Dolby Digital True HD and DTS-HD Master Audio
- High-quality connectors – 24K gold-plated, corrosion-resistant and best possible connectivity
- Pull-resistant – K-Lock connectors with 15lbs of restraining force
- EMI & RFI Immunity
- No External Power – Powers the active units via the HDMI connector
- Thin Construction – 4.5mm (0.18”) diameter.
- Small Bending Radius – Only 6mm (0.24”).
- Jacket Construction – TPU (Thermoplastic Polyurethane).
- RoHS 2011/65/EU compliant
- Varied Selection of Lengths – Available in versions from 10 to 100m (33 to 328ft)

### In the Box

- 1x active Optical High-Speed HDMI Cable
- 2x HDMI type-D to A adapter
- 2x HDMI-A end locking screw
- 1x USB-A to MicroB cable
- 1x pulling capsule
- 1x User manual





## CABLE SPECIFICATIONS

### AUDIO & VIDEO SPECIFICATIONS

<b>Video Resolution</b>	4K@60Hz 4:2:0, 4K@30Hz 4:4:4, 8Bit, full HD, 3D Deep Color
<b>Data Rate (max)</b>	Up to 10.2 Gbps
<b>Supported Color Spaces</b>	RGB, YCbCr, xvYCC, Adobe sRGB, sYCC601
<b>Embedded Audio</b>	Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio™, DVD Audio, SA-CD
<b>HDMI Compliance</b>	HDCP 2.2, EDID, CEC

### PHYSICAL SPECIFICATIONS

<b>Connector-1 (source end)</b>	Male HDMI type-A 24K gold plated (pluggable) / Male HDMI type D
<b>Connector-2 (display end)</b>	Male HDMI type-A 24K gold plated (pluggable) / Male HDMI type D
<b>Cable Structure</b>	Hybrid Optical Fiber Cable
<b>Fiber Optic <b>A</b></b>	Multi-mode fiber
<b>Conductors <b>B</b></b>	6x28AWG (7/0.127mm)
<b>Outer Sheath Material <b>C</b></b>	TPU (Thermoplastic Polyurethane)
<b>Outer Sheath Color</b>	Black
<b>Outer Sheath Diameter</b>	4.5mm
<b>Cable Bending Radius</b>	6mm
<b>Connector Max. Pulling Strength</b>	22lbs/10kg
<b>Max. Compression Load Resistance</b>	500N (50kg, 110lbs)

### POWER SPECIFICATIONS

<b>Power Supply</b>	No external power supply is needed (draws current from the source). If source power is not sufficient, connect the supplied USB cable to an external power.
<b>Power Consumption</b>	0.25W max






### ENVIRONMENTAL SPECIFICATION

<b>Operating Temperature</b>	+32~+122°F (0~+50°C)
<b>Storage Temperature</b>	-22~+122°F (0~+50°C)
<b>Operating Humidity</b>	5 ~ 85%




### REGULATORY

<b>RoHS</b>	2011/65/ EU
-------------	-------------

## OUTLINE DIMENSIONS



## Pulling Capsule Dimensions





## ORDERING INFORMATION

MODEL	DESCRIPTION	LENGTH	GROSS WEIGHT
<b>CRS-AOCH/XL-33</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	33ft/10.00m	1.10lbs/0.5kg
<b>CRS-AOCH/XL-50</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	50ft/15.20m	1.34lbs/0.61kg
<b>CRS-AOCH/XL-66</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	66ft/20.00m	1.59lbs/0.72kg
<b>CRS-AOCH/XL-98</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	98ft/30.00m	2.09lbs/0.95kg
<b>CRS-AOCH/XL-131</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	131ft/40.00m	2.58lbs/1.17kg
<b>CRS-AOCH/XL-164</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	164ft/50.00m	3.22lbs/1.46kg
<b>CRS-AOCH/XL-197</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	197ft/60.00m	3.70lbs/1.68kg
<b>CRS-AOCH/XL-230</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	230ft/70.00m	4.21lbs/1.91kg
<b>CRS-AOCH/XL-262</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	262ft/80.00m	4.70lbs/2.13kg
<b>CRS-AOCH/XL-295</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	295ft/90.00m	5.20lbs/2.36kg
<b>CRS-AOCH/XL-328</b>	Rental & Staging Active Optical High-Speed Pluggable HDMI Cable	328ft/100.00m	5.69lbs/2.58kg

