

POWER

Sold as:	Each
Color:	Black housing and gray safety slides
Number Of Outlets	8 (3 Spaced)
Maximum Current Rating	15A
Peak Surge Current (Amps)	105K
Line Voltage	125V AC 60 Hz
Single Pulse Energy Dissipation (Joules)	2,100
EMI / RF Noise Filtration (dB)	50
Noise Filtration Range	100KHz - 1MHz
Safety Listing Compliance	UL
UL 1283 Listed	Y
UL 1363 Listed	Y
UL 1449 Listed	Y
UL 1449 Suppression Rating	L-N : 330V L-G : 500V N-G : 500V
Power Cord Length (Ft)	4
Weight	1.69 lbs (.76 kg)
Dimensions	3.74" (95 mm) X 4.84"(123mm) X 1.73" (44mm)
Transient Response Time (Ns)	> 1 nanosecond

COAXIAL

Number of Pairs	1
Surge Shielded Protection	Yes
Coaxial Insertion Loss	> 1.0 dB
Frequency Range	0 -3.0 GHz
HD 1080P Ready?	Yes
Coaxial Breakdown Voltage	90V
Coaxial Bidirectional?	Y
Gold Plated "F" Connectors	Y

TELCO / LAN

RJ-11 Number Of Telecom Connector Pairs	0
RJ-11 Telecom Clamping Level	N/A
RJ-11 Telecom Capacitance	N/A
RJ-45 Number Of LAN Connector Pairs	1
RJ-45 LAN Clamping Level	6.8V
Connected Equipment Guarantee Amount	\$5,000