

AC Power

Line Voltage	120V, 60Hz
AC Input Connection	IEC C-14
Power Cord Length	4 Feet
Breaker/Switch Rating	15A
UL Current Rating	12A
Voltage Protection Rating (UL 1449 3rd Edition)	500V
Joule Rating	2160 Joules
Surge Component	Ceramic Encased MOV
Protection Modes	L-N, L-G, N-G
Peak Impulse Current	48,000A
Disconnect Circuitry	Yes
Thermal Fuse	Yes

EMI / RFI Noise Filtration

All Outlets	53 dB, 300KHz to 50 MHz
-------------	-------------------------

UL Certifications

UL 60950-1, UL 1449, UL 498, UL 497A/B, UL 1283

Cable / Satellite Circuit

Connections	Gold Plated "F" Connector
Surge Component	Gas Tube
Clamping Voltage	600V
Frequency Range	0MHz - 3.0 GHz
Insertion Loss	< 0.5 dB
Shielded	Yes
Bi-directional	Yes

Phone / LAN Circuit

Jacks	RJ45
Accepts	RJ11 & RJ45
Surge Component	Sidactor & MOV
Clamping Voltage	RJ11:500V; RJ45:250V
Wires Protected	8 Wires

Outlets

Type	NEMA 5-15
Numer of Outlets	4
Switched	All