

## Specifications

### AC Power

|   |  |
|---|--|
| Line Voltage                                    | 120V, 60Hz   |
| AC Input Connection                             | IEC C-14   |
| Power Cord Length                               | (1) 4 Foot with 360° Rotating Flat Plug; (1) 6 in. (for use when mounted in enclosure), (1) 6 in. extension cord |
| Breaker/Switch Rating                           | 15A  |
| UL Current Rating                               | 12A  |
| Voltage Protection Rating (UL 1449 3rd Edition) | 500V   |
| Joule Rating                                    | 2160 Joules  |
| Surge Component                                 | Ceramic Encased MOV  |
| Protection Modes                                | L-N, L-G, N-G  |
| Peak Impulse Current                            | 48,000A  |
| Disconnect Circuitry                            | Yes  |
| Thermal Fuse                                    | Yes  |

### EMI / RFI Noise Filtration

|             |                     |
|-------------|---------------------|
| All Outlets | 53 dB, 1kHz to 1MHz |
|-------------|---------------------|

### Cable / Satellite Circuit

|                  |                           |
|------------------|---------------------------|
| Connections      | Gold Plated "F" Connector |
| Quantity         | 2 (1 Input and 1 Output)  |
| Surge Component  | Gas Tube                  |
| Clipping Voltage | 600V                      |
| Frequency Range  | 0MHz - 3.0 GHz            |
| Insertion Loss   | < 0.5 dB                  |
| Shielded         | Yes                       |
| Bi-directional   | Yes                       |

### Phone / LAN Circuit

|                  |                          |
|------------------|--------------------------|
| Jacks            | RJ45                     |
| Accepts          | RJ11 & RJ45              |
| Quantity         | 2 (1 Input and 1 Output) |
| Surge Component  | Sidactor & MOV           |
| Clipping Voltage | RJ11:500V; RJ45:250V     |
| Wires Protected  | 8 Wires                  |

### Outlets

|                  |           |
|------------------|-----------|
| Type             | NEMA 5-15 |
| Numer of Outlets | 6         |

### Operating Temperature Range

|                            |
|----------------------------|
| 14 to 104°F (-10 to +40°C) |
|----------------------------|

### UL Certifications

|   |
|---|
| UL 60950-1, UL 1449, UL 498, UL 497A/B, UL 1283 |
|---|

### Dimensions

|                                      |
|--------------------------------------|
| 7.9"W x 2.7"H x 6.3"D (w/o brackets) |
|--------------------------------------|