

# Specifications

<b>Dimensions:</b>	Length: 131mm (5.1 in) Depth: 79mm (3.1 in with plugs) (1.5 in without plugs) Height: 57mm (2.24 in) Weight: 0.44 lbs. (0.2 kg)
<b>Number Of Outlets</b>	3
<b>Number Of Coaxial Outlets</b>	1
<b>Maximum Current Rating</b>	15A
<b>Line Voltage</b>	120V AC 60 Hz
<b>Peak Impulse Current (Amps)</b>	72,000
<b>Single Pulse Energy Dissipation (Joules)</b>	1,080
<b>EMI / RF Noise Filtration (dB)</b>	70
<b>Noise Filtration Range</b>	150KHz - 100MHz
<b>Compliance</b>	UL + CUL
<b>UL 498 &amp; 498A Listed (Receptacle and attachment plugs) (Current taps and adpators)</b>	Y
<b>UL 1449 Listed (Transient Voltage Surge Suppressors)</b>	Y
<b>UL 1449 Listed (AC Power Suppression Rating)</b>	400V
<b>Transient Response Time (ns)</b>	> 1 nanosecond
<b>Coaxial Cable Length (Ft)</b>	6
<b>Operating Temperature</b>	Normal 85 ~ 95 degrees F Full Load 118 degrees F
<b>Weight</b>	0.44 lbs (.2 kg)
<b>Frequency Range</b>	300MHz - 2.2GHz
<b>Coaxial HD 1080p Ready?</b>	Yes
<b>Coaxial Breakdown Voltage</b>	75V
<b>Coaxial Gold Plated "F" Connectors</b>	Y
<b>Coaxial Surge Shielded Protection</b>	Y
<b>Coaxial Insertion Loss</b>	>0.1 dB
<b>Coaxial Bidirectional</b>	Y
<b>Connected Equipment Guarantee</b>	\$5,000