

AC Power

Line Voltage	120V, 60Hz
AC Input Connection	IEC C-14
Power Cord Length	6 Feet
Circuit Breaker Rating	15A
UL Current Rating	12A
Voltage Protection Rating (UL 1449 3rd Edition)	500V
Joule Rating	6480 Joules
Surge Component	Ceramic Encased MOV
Protection Modes	L-N, L-G, N-G
Peak Impulse Current	396,000A
Disconnect Circuitry	Yes
Thermal Fuse	Yes

Safe Voltage Disconnect

Over Voltage	138 VAC + 5 VAC
Under Voltage	88 VAC + 5 VAC

EMI / RFI Noise Filtration

Filter Banks 1 & 2	80 dB, 300 kHz to 100 MHz
Filter Bank 3 (High Current)	80 dB, 300 kHz to 100 MHz

DC Trigger

Jacks	3.5 mm (1/8") mono mini plug
Input	
Voltage	3 - 24 VDC, Bidirectional
Current	3mA @ 3V, 30 mA @ 24V

Output

Pass Through	No Delay
Output Voltage	12 VDC
Positive	Tip
Negative	Ring

Cable / Satellite Circuit

Connections	Gold Plated "F" Connector
Surge Component	Gas Tube
Clamping Voltage	600V
Frequency Range	0MHz - 3.0 GHz
Insertion Loss	< 0.5 dB
Shielded	Yes
Bi-directional	Yes

Phone / LAN Circuit

Jacks	RJ45
-------	------

Accepts	RJ11 & RJ45	
Surge Component	Sidactor & MOV	
Clamping Voltage	RJ11:400V; RJ45:250V	
Wires Protected	8 Wires	
Outlets		
Type	NEMA 5-15	
Numer of Outlets		12
Always On	Bank 1 (4 Outlets)	
Switched	Bank 2 (4 Outlets)	
Delayed (5 sec.)	Bank 3 (4 Outlets)	
Display Link Outputs		
Display Communication	RJ45	
Display Power	NEMA 5-15	
UL Certifications		
UL 60950-1, UL 1449, UL 498, UL 497A/B, UL 1283		