

# WIREFATH

## BULK WIRE

### SP-LUT1-1000 or -500

22AWG, 2 Conductor Shielded + 18AWG, 2 Conductor Unshielded, CL3

### Features

- Oxygen - Free Copper conductors ensure signal integrity
- Designed for short- and medium-length runs

### Application


- Power limited circuit cable for use as fixed wiring within buildings principally for class 3 and class 2 circuits.
- Control system applications such as Crestron, Lutron, and AMX
- Transfers data and power over a single bundle

### Flame Test

- UL & C(UL) Flame Test: CL3 & FT4
- Rated Temp: 75°C
- Rated Voltage: 300V
- Production Standard: UL 444
- UL Certification: (UL) and c(UL) CL3

### Applicable Standards

- |                           |     |
|---------------------------|-----|
| • NEC/(UL) Specifications | CL3 |
| • NEC Articles            | 725 |
| • CEC/(UL) Specifications | CL3 |



# WIREFATH

## BULK WIRE

Material and Construction		
Component A		2X22AWG shielded
Cond. Material	Oxygen Free Copper Wire	
AWG	22 (7/0.25mm)	
Insulation Material	Foamed PE with Skin	
Insulation Diameter	1.8mm ± 0.2mm	
Insulation thickness	0.60 ± 0.15mm	
Insulation Color	White / Blue	
Drain wire	7/0.20TC	
Al-foil shielding	100% Coverage	
Component B		2X16AWG unshielded
Cond. Material	Oxygen Free Copper Wire	
AWG	16 (26/0.25mm)	
Insulation Material	SR PVC	
Insulation Diameter	2.15mm ± 0.2mm	
Insulation thickness	0.35 ± 0.10mm	
Insulation Color	Red / Black	
Components A & B Combined Together		
Rip Cord	150D*3	
Jacket	PVC	
	Outer Diameter	5.8mm
	Norm. Thickness	0.65mm
Marking	WIREFATH™ BULK WIRE BY SNAPAV LUT1 OXYGEN FREE COPPER 16AWG 2C + 22AWG 1PR SHIELDED E325181-HY (UL) CL3 or E325177-HY c(UL) CL3 FT4 75C DDMMYY “ROHS” XXX/XXX FT	

# WIREFATH

## BULK WIRE

### Performance

Physical & Electrical Characteristics (at 20°C)

Component A	Impedance	100 ± 15 Ohms
	Capacity	11 ± 2 Pf/feet
Cond. DCR	16AWG	≤ 13.7 Ohms/KM
	22AWG	≤ 55.4 Ohms/KM

### Color and Packaging

Component A	White & Blue
Component B	Black & Red
Jacket	Non Brightness Blue: Pantone 279U
	with Orange: Pantone 1505 Stripe
Packaging	500 or 1000ft. on Spool
Dimensions (in)	15.0" x 7.1" x 5.9"
Dimensions (mm)	380mm x 180mm x 150mm
Weight (lbs)	45
Packaging	500ft. on Spool
Dimensions (in)	10.6" x 7.1" x 4.3"
Dimensions (mm)	270mm x 180mm x 110mm
Weight (lbs)	22

Values above 250MHz are for information only.